



NEW
addition to the range!

FRAMEX HS 180

INNOVATIVE LIFT-AND-SLIDE ALUMINUM SYSTEM
WITH THERMAL BREAK

Ideal for glazing large openings

CONTACT US

tel.: +49 305 201 51 23

e-mail: info@framex-systeme.de

SCAN HERE

for detailed
information



framex-system.com

FRAMEX HS 180

LIFT-AND-SLIDE ALUMINUM SYSTEM WITH THERMAL BREAK



- Energy efficiency and high thermal resistance;
- Easy opening thanks to the latest hardware from leading European suppliers;
- Reinforced profile allowing the production of large constructions up to 3200 mm in height;
- Reliable wind insulation through an additional connection contour;
- The drainage system and the use of sealing inserts provide protection for structures against water penetration;
- A wide range of frame options: monorail, dual-rail, with and without a mounting flange;
- Contributes to adhering to the principles of inclusion, providing convenient barrier-free access;
- Integration into **TM Framex** facade systems;

TECHNICAL SPECIFICATIONS

Mounting depth of the frame	180 mm, 186 mm
Mounting depth of the sash	80 mm
U _f	1,2 W/m ² K
U _g	0,5 W/m ² K
U _w	0,8 W/m ² K
Thickness of the glazing unit	34-64 mm
Number of sashes in the structure	1, 2
Thermal bridge	up to 46 mm
Maximum weight of the sash	400 kg
Max. dimensions of the sash	3000x3200 mm
Max. width of the structure	6500 mm

